



The Super L VI is ideal for your most demanding work!



Choice of pointing devices (see features)

Overview

The Super L VI is the next generation of the well-known Super L Series family of digitizers—digitizers that set the standard in large format digitizing. Professionals in construction estimating, CAD, textiles and other will appreciate the added and improved performance of the Super L VI series. The Super L VI systems now include an integrated USB connection that allows the digitizer to be powered from the USB port of the computer. When the Super L VI is connected via the integrated RS-232 Serial connection, or with the QuikRuler, an optional power supply is required.

With a resolution of up to 2540 lines-per-inch and accuracy of 0.010", the Super L VI is ideal for your most demanding work. Super L VI allows you to select a corded or cordless transducer—whichever suites your preference and your project. In addition, the transducers are available in your choice of two different styles, offering you the chance to select the style that is most comfortable for your hand. Whether you choose the 4- or 16-button cursor or the stylus pen, you don't have to compromise comfort for performance!

Super L VI's improved driver set, provided on CD in a user-friendly interface, makes set-up even easier. Custom configurations, previously available through the tablet hardware, are now available through a software configuration program that supports emulations of popular industry formats, including CalComp 3400 and Summagrid.

Features

Choice of pointing devices

- 16-button cursor, corded or cordless
- 4-button diamond cursor, corded or cordless
- Click tip pen, corded or cordless

Compatibility

- GTCO Type 5/5A
- Summagraphics
- CalComp
- Ensures compatibility with virtually all software packages

Accurate

- Patented sensing technology provides up to 1/2540" (1/100mm) resolution
- ± 0.01" (0.25mm) accuracy

Easy to Use

- Integrated USB connection allows digitizer to be powered through USB port on connected computer
- Software for RS-232 Serial connection can be quickly reloaded with GTCO CalComp's SuperSet™ Menu
- SuperSet™ allows users to quickly switch between applications

Lightweight

- Lightest weight rigid tablet available today
- Provides quick and easy set-up

Durable and Dependable

- State-of-the-art materials
- Durable, tough work surface
- Backed by a two-year limited warranty

Specifications

Platform Support	PC
Software Drivers	Microsoft Windows 95, 98, ME, NT, 2000, XP, Vista, and 7
Hardware Interface	USB, RS-232 and QuikRuler Port (Requires optional Power Supply)
Accuracy	±0.010 in/0.25 mm
Resolution	Up to 2,540 lines-per-inch/100 lines-per-mm
Proximity	1.0 in/25.4 mm with corded transducers 0.4 in/10.16 mm with cordless transducers
Baud Rate	Up to 38,400
Data Rate	Up to 200 coordinate pairs per second
Technology	Electromagnetic
Output Formats	GTCO Type 5/5A, Summagraphics, CalComp
Operating Modes	Line, continuous, line increment and continuous increment
Power Supply	120 V/60 Hz, 220 V/50 Hz (required for RS-232 serial connection) No supply required for USB connection
Power Requirements	5 Volts, DC, 100 mA current draw (USB) 9 Volts, DC, 200 mA current draw (with Power Supply)
Certification	UL 1950, EN60950, FCC, VCCI, CE, EN55024, EN55022, Industry Canada
Operating Temperature	50 to 104°F/10 to 40°C
Storage Temperature	-40 to +158°F/-40 to +70°C
Humidity Range	0 to 95%, noncondensing
Operating Altitude	Up to 15,000 ft/4,600 m
Storage Altitude	Up to 50,000 ft/15,200 m
Warranty	Two-year limited warranty; extended warranty available—U.S. only

Included With Your Purchase
 Super L VI tablet and controller
 Corded or cordless transducer
 (as specified at time of order)
 CD ROM with Software Drivers
 and Electronic Users Manual
 USB Cable
 Table feet (non bracket systems only)

Transducer Options
 16-button cursor, corded or cordless
 4-button cursor, corded or cordless
 Click tip stylus, corded or cordless
 Inking inserts for corded stylus

Other Options
 Plan hold down or clamps
 Clear overlay
 QuikRuler III Measuring Module
 Universal mounting brackets
 Manual lift/manual tilt pedestal
 RS-232 Kit
 (Power Supply and I/O Cable)
 Adjustable table feet
 Pen Tray
 Extended warranty

Tablet Options and Physical Dimensions

Model	Active Area	Footprint	Weight	Average Shipping Weight
SL6-2024	20 x 24 in/508 x 610 mm	29 x 34 in/737 x 864 mm	13 lb/5.9 kg	31 lb/14.1 kg
SL6-2436	24 x 36 in/610 x 914 mm	32.5 x 46 in/826 x 1,168 mm	19 lb/8.6 kg	42 lb/19.1 kg
SL6-3036	30 x 36 in/763 x 914 mm	35.3 x 44.5 in/896 x 1,130 mm	19 lb/8.6 kg	42 lb/19.1 kg
SL6-3648	36 x 48 in/914 x 1,219 mm	44.5 x 60 in/1,130 x 1,524 mm	30 lb/13.6 kg	70 lb/31.8 kg
SL6-4460	44 x 60 in/1,117 x 1,524 mm	52.5 x 69 in/1,333 x 1,753 mm	40 lb/18.2 kg	80 lb/36.4 kg

Pricing

All units include Digitizer Tablet, USB connections, One Pointing Device, Drivers, and User Guide

Model	Digitizer for Existing Software	Digitizer Systems: With QuikRuler	With Crystal Takeoff	With Power Takeoff
2024	\$2,095.00*	\$2,445.00*	\$2,390.00	\$2,695.00
2436	\$2,395.00*	\$2,745.00*	\$2,690.00	\$2,990.00
3036	\$2,395.00*	\$2,745.00*	\$2,690.00	\$2,990.00
3648	\$2,795.00*	\$3,145.00*	\$2,990.00	\$3,290.00
4460	\$3,195.00*	\$3,545.00*	\$3,290.00	\$3,590.00



***Call for Special Pricing**